## **EUCLID BRAKE CHAMBERS**






Euclid brake chambers are trusted as a quality product for the drum brake aftermarket. Designed to meet SAE J2318 requirements, the chambers are engineered and built for performance. Chambers are available with clevis as well as the release tool and holder. Euclid chambers are available in tandem, piggyback, and service chamber designs and in a variety of sizes and stroke lengths. Quality is ensured with a 3 year warranty.

Euclid Brake Chambers					
PART NUMBER	DESCRIPTION	STROKE	PUSH ROD THREAD SIZE	CLEVIS INCLUDED	UNIT PACK
E-BC2024C	Sealed Spring Brake Combination Unit for S-Cam Brakes (2024)	Standard 2.5 in.	5/8 in18	Y(1)	1
E-BC2424C	Sealed Spring Brake Combination Unit for S-Cam Brakes (2424)	Standard 2.5 in.	5/8 in18	Y(1)	1
E-BC2430C	Sealed Spring Brake Combination Unit for S-Cam Brakes (2430)	Standard 2.5 in.	5/8 in18	Y(1)	1
E-BC2430C-EL	Sealed Spring Brake Combination Unit for S-Cam Brakes (2430L)	Long Stroke 3 in.	5/8 in18	Y(1)	1
E-BC3030C	Sealed Spring Brake Combination Unit for S-Cam Brakes (3030)	Standard 2.5 in.	5/8 in18	Y(1)	1
E-BC3030CPLBX	Sealed Spring Brake Combination Unit for S-Cam Brakes (3030)	Standard 2.5 in.	5/8 in18	Y(1)	50
E-BC3030C-EL	Sealed Spring Brake Combination Unit for S-Cam Brakes (3030L)	Long Stroke 3 in.	5/8 in18	Y(1)	1
E-BC3036C	Sealed Spring Brake Combination Unit for S-Cam Brakes (3036)	Standard 2.5 in.	5/8 in18	Ν	1
E-BC3636C	Sealed Spring Brake Combination Unit for S-Cam Brakes (3636)	Standard 2.5 in.	5/8 in18	N	1
E-BC3030P-L	Sealed Spring Brake Piggyback Unit for S-Cam Brakes	Standard 2.25 in.	N/A	N	1
E-BC3030PK-L	Sealed Spring Brake Piggyback KIT for S-Cam Brakes with Diaphragm, Clamp, & Bolts	Standard 2.25 in.	N/A	Ν	1
E-BC3030P-EL	Sealed Spring Brake Piggyback Unit for S-Cam Brakes	Long Stroke 3 in.	N/A	Ν	1
E-BC3030PK-EL	Sealed Spring Brake Piggyback KIT for S-Cam Brakes with Diaphragm, Clamp, & Bolts	Long Stroke 3 in.	N/A	N	1
E-BC12S	Brake Service Chamber for S-Cam Brakes (Type 12)	Standard 1.75 in.	1/2 in20	Y(2)	1
E-BC16S	Brake Service Chamber for S-Cam Brakes (Type 16)	Standard 2.25 in.	1/2 in20	Y(2)	1
E-BC20S	Brake Service Chamber for S-Cam Brakes (Type 20)	Standard 2.25 in.	5/8 in18	Y(1)	1
E-BC24S	Brake Service Chamber for S-Cam Brakes (Type 24)	Standard 2.25 in.	5/8 in18	Y(1)	1
E-BC24S-EL	Brake Service Chamber for S-Cam Brakes (Type 24L)	Long Stroke 3 in.	5/8 in18	Y(1)	1
E-BC30S	Brake Service Chamber for S-Cam brakes (Type 30)	Standard 2.5 in.	5/8 in18	Y(1)	1
E-BC30S-EL	Brake Service Chamber for S-Cam brakes (Type 30L)	Long Stroke 3 in.	5/8 in18	Y(1)	1
E-8890	Type 16 Brake Chamber Diaphragm	N/A	N/A	Ν	4
E-8891	Type 20 Brake Chamber Diaphragm	N/A	N/A	Ν	4
E-8892	Type 24 Brake Chamber Diaphragm	N/A	N/A	Ν	4
E-11888	Type 24 Long Stroke Brake Chamber Diaphragm	N/A	N/A	Ν	10
E-8894	Type 30 Brake Chamber Diaphragm	N/A	N/A	Ν	4
E-11889	Type 30 Long Stroke Brake Chamber Diaphragm	N/A	N/A	Ν	4
E-8895	Type 36 Brake Chamber Diaphragm	N/A	N/A	N	4

<sup>(1)</sup> Clevis: 5/8 in.-18, 1/2 in. pin.

<sup>(2)</sup> Clevis: 1/2 in.-20, 1/2 in. pin.





Double O-ring and bushing structure provide enhanced leak protection and wear resistance

Premium diaphragm ensures 1.2 million life cycles


Premium diaphragm ensures 500,000 parking life cycles

Performance grade spring material delivers linear output



Aluminum design is both lightweight and high-strength

E-coating is applied for excellent corrosion protection







Meritor Heavy Vehicle Systems, LLC 7975 Dixie Highway Florence, KY 41042 U.S. 888-725-9355 Canada 800-387-3889 MeritorPartsXpress.com ©2018 Meritor, Inc. Litho in USA Revised 08-18 SP-1688 (47865/11900)